



## Toyota Land Cruiser Series 75 & 78 – gullwing window glass (rear side)

Dark-tinted safety glass for the rear side panel.  
Polished edges, watertight seal, and fast access to  
gear — purpose-built for overland conditions.

## Specifications

Article number	EXG-REAR-TOY-TROOP
Price	Price starts from €470,-
Dimensions	Width: 846mm Height: 422mm
Suitable for	Toyota - Toyota Land Cruiser Series 78 Troop Carrier Toyota - Toyota Land Cruiser Series 75 Troop Carrier

## Toyota Land Cruiser Series 75 & 78 – gullwing window glass (rear side)

A gullwing window in dark-tinted safety glass, tailored for the rear panel of the Toyota Land Cruiser 75 or 78 Series. It replaces the factory rear side window and offers quick, unobstructed access to gear, storage, or recovery equipment via an upward-opening hatch.

Installation requires no body modifications. Only the outer flange — where the original glass was seated — needs to be flattened for a proper seal. Once installed, the unit blends cleanly with the vehicle's body, maintaining an OEM-style appearance.

### Key Features

- Flip-up design in 5 mm toughened glass
- Smooth upward opening supported by gas struts
- Lockable compression latches for secure sealing
- Dust- and watertight construction
- Mounted in the original rear side window position
- Fully preassembled for fast installation

### Construction

- Glass type: 5 mm tempered safety glass
- Certification: ECE 43R and DOT approved
- Edge finish: polished
- Tint: LT20% dark grey
- Frame: black powder-coated aluminium (RAL 9005)
- Closure: two lockable compression latches
- Opening mechanism: two pre-installed gas struts
- Sealing: multi-chamber TPE insert rubber

### Dimensions



- Width: 846 mm
- Height: 422 mm
- Dimensions refer to the internal fitting size. The outer frame extends 15 mm beyond this on all sides.
- Location: rear side panel

## Compatible Accessories

[Window guard \(mounts directly onto the glass surface\)](#)

[Explore Overlander Light \(fold-down table and guard in one\)](#)

All accessories are engineered specifically for Explore Glazing gullwing windows and are not compatible with factory or third-party systems.



## Installation

The gullwing window is installed in place of the original rear side window. The flange of the body where the factory glass was installed is slightly curved and must be flattened to ensure a reliable and even seal. The inner and outer body panels are spot-welded, which may cause slight variation in window cut-out dimensions. Carefully centre the window before fastening.

The window is sealed with a closed-cell neoprene foam insert and fixed using stainless steel M4x20 screws and adhesive. No cutting or welding required. Supplied fully preassembled.

A mounting kit is available on request and includes:

- Ø 4.2 mm drill bit
- Cartridge of Dowsil 791
- Application brush
- Sealant finishing rubber tool

Black powder-coated stainless screws are available as an option and are quoted by default.

Installation should be carried out with care. Incorrect mounting can lead to leaks or improper alignment. Assembly videos can be found on the Explore Glazing YouTube channel.

[@ExploreGlazing](#)

## Images

